

AMANO[®]

ELECTRONIC TIME RECORDER

BX1600

ECONOMICAL TIME RECORDER
WITH VALUABLE FEATURES

High-quality dot matrix printer

Printing irregular mark

Programmable IN/OUT Printing position

6 column printing

MAIN FEATURES

- Simple, clean design fits any business environment
- Lithium battery holds memory up to 3 years
- Large, easy-to-read digital clock face with quartz time base
- Surface detection function for right side of time card
- Automatic adjustment of Daylight-Saving Time, short months, leap years
- Automatic card feeding, standard
- Programmable IN/OUT printing position



No. <u>1/1/</u>		PAY ENDING <u>May</u> , 20 <u>05</u>					
NAME <u>Carlos Lopez</u>							
	HOURS	RATE	AMOUNT	DEDUCTIONS	INCOME TAX	\$180.00	
R.T.	186.5	\$6.00	\$1,119.00		UNEMP. INS.	\$20.00	
O.T.	10	\$9.00	\$90.00		HOSP.		
					BONDS		
					MISC.		
TOTAL EARNINGS			\$1,209.00				
TOTAL DEDUCTIONS			\$200.00				
BALANCE DUE			\$1,009.00		TOTAL	\$200.00	
DATE	MORNING		AFTERNOON		OVERTIME		HOURS
	IN	OUT	IN	OUT	IN	OUT	
1	8:29	12:02	12:58	17:36			8
2	8:34	12:03	12:57	17:39	17:45	19:46	9.5
3	8:27	12:01	12:54	17:33			8
4	8:29	12:04	13:02	17:38			7.5
5	8:28	12:10					3.5
6							
7	8:28	12:01	12:58	15:00			5.5
8	8:28	11:55	12:58	17:36			8
9	8:29	12:03	12:59	17:31	18:00	20:03	9.5
10	8:24	12:04	12:58	17:37			8
11	8:29	12:01	12:58	17:36			8
12	8:27	12:03					3.5
13							
14	8:22	12:08	12:58	17:32			8
15	8:29	12:01	12:55	17:38			8
THE BALANCE SHOWN ABOVE IS CORRECT AND RECEIPT IS ACKNOWLEDGED.							
SIGNATURE				<u>Carlos Lopez</u>			
AMANO FORM A-701							

Acceptable Pay Period

Pay period can be set three ways.

- weekly
- bi-weekly
- semi-monthly/monthly

BASIC SPECIFICATIONS

Printing	Dot matrix printing
Power Supply	110/120VAC or 220/240VAC+10% 50/60Hz
Power Consumption	110-120VAC... Stand-by 70mA, Rated 120mA 220-240VAC... Stand-by 60mA, Rated 80mA
Operating Conditions	Temperature: -10°C to 40°C Humidity 10% to 90% RH (without condensation)
Dimensions	190(W) X 224(H) X 104(D)mm (7.1/2" X (8.6/8") X (4")
Clock System	Quartz oscillation system, Accuracy=3 seconds per week(25°C±5°C)(77°F±10°F)
Weight	2.3Kg(5.1Lbs.)
Memory holding function	Clock and programing data kept for 3 years without AC power

Specifications and descriptions contained in this catalog may be subject to change without notice.

Distributed by:

AMANO Corporation

275 MAMEDO-CHO, KOHOKU-KU, YOKOHAMA,
JAPAN 222-0558
TEL.+81-45-439-1508 FAX.+81-45-439-1151
HOME PAGE: <http://www.amano.co.jp/> English